



F5317 ~X37CrMoSiV5 / W.Nr. ~1.2343

Barras redondas IBO ECOMAX

Acabado: laminado o forjado, descortezado o bien torneado

172	202	242,0	262,0	282,0	303	323	373	423	503	553	652	703	753	803	853
-----	-----	-------	-------	-------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Barras redondas convencionales

Acabado: descortezado o bien torneado

15,0	20,5	26,0	31,0	36,0	41,0	46,0	51,0	56,0	61,0	66,0	71,0	76,0	81,0	91,0	96,0	101,0	111,0	121,0	131,0
141,0	151,0	161,0	172,0	182,0	192,0	202,0	207,0	212,0	222,0	232,0	237,0	242,0	252,0	262,0	282,0	292,0	303,0	313,0	323,0
333,0	353,0	363,0	373,0	378,0	383,0	403,0	413,0	423,0	443,0	453,0	483,0	503,0	523,0	543,0	563,0	583,0	603,0	663,0	

Acero para trabajo en caliente

Barras planas ESR

Acabado: laminado o forjado
todas las superficies mecanizadas

ancho mm	espesor mm																										
	100	110	120	130	140	150	160	170	180	190	205	225	255	275	305	325	355	365	375	405	425	450	455	505	550	600	
500	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		X	X							
710																						X					
810																		X									
850	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		X								
1010	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		X	X	X			X	X	X	X
1450																				X							

Barras planas convencionales

ancho mm	espesor mm																													
	20	25	30	35	40	45	50	55	60	70	80	90	100	110	120	130	140	150	160	175	185	195	205	215	235	245	255	305	355	405
160	X		X		X		X		X	X	X	X	X																	
200	X		X		X		X		X	X	X	X	X																	
250	X	X	X		X		X		X	X	X	X	X																	
300	X	X	X		X		X		X	X	X	X	X																	
350			X		X		X		X	X	X	X	X																	
400		X	X		X		X		X	X	X	X	X																	
450					X		X		X																					
500													X																	
1010	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
1250			X		X		X		X	X	X	X	X	X	X															
1600					X		X		X				X																	
2000											X	X	X																	

Nota: para información sobre tolerancias y acabados, rogamos consulten